

Click on products for more information

5-10 Watts	10-12 Watts	12-18 Watts	20-36 Watts	36-60 Watts	60-120 Watts	120-1000 Watts	1200-3000 Watts	240-800 Watts
<p>GT-83083-0505-USB 5 Watts Vout=5 49.2 x 47.0 x 27.5</p>	<p>GT-86120-WWVV 10 Watts Vout=5, 12 70(L) x 32.8(W) x 48.5(H)</p>	<p>GT-86120-WWVV-X.X-W2E 12 Watts Vout=5, 12 69 x 28.8 x 58.3</p>	<p>GTM93021-20VV-P2 20 Watts Vout=5-48</p>	<p>GTM96300-36VV-R2/R3A 36 Watts Vout=5-48 74 x 43.5 x 36.8</p>	<p>GTM96600-60VV-R 60 Watts Vout=5-48 117.53 x 53.47 x 36.6</p>	<p>GTM43004P-WWVV-X.X-P3 120 Watts Vout=5-48</p>	<p>GTM63073P1200VV-X.X 1200 Watts Vout=12-60</p>	<p>GTM95600-BWWVV-F 60 Watts Vout=5-48 101.6 x 50.8 x 30.5</p>
<p>GTM96060-06VV-Q 6 Watts Vout=3.3-48 43.5 x 74.0 x 36.8</p>	<p>GTM46101-10VV-X.X-USB 10 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p>GTM46161-16VV-X.X-USB 16 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p>GT-46240-24VV 24 Watts Vout=12-24 80.6 x 50.0 x 31.0</p>	<p>GT-96300-3656-AP 36 Watts Vout=56 107 x 55 x 36</p>	<p>GTM91099-60VV-P3 60 Watts Vout=5-48</p>	<p>GTM961500P-150VV 150 Watts Vout=12-54 173 x 72 x 38</p>	<p>GT-G3060P1500VV-X.X-C 1500 Watts Vout=12-60</p>	<p>GTM96700-BWWVV-F 70 Watts Vout=5-48 101.6 x 50.8 x 30.5</p>
<p>GT-46060-06VV-X.X-Q 6 Watts Vout=5-24 40.5 x 64.0 x 30.0</p>	<p>GT-86120-WWVV-X.X-W2C 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p>GT-96180-1856-R2-AP 18 Watts Vout=56</p>	<p>GT-86240-WWVV-X.X 24 Watts Vout=12 73.5 x 35 x 57</p>	<p>GT-46401-40VV-X.X-Q 40 Watts Vout=12-48 90.0 x 38.0 x 59.4</p>	<p>GT-96600-7056-T3-AP 70 Watts Vout=56</p>	<p>GT-G3068P650VV-X.X-C 650 Watts Vout=5-48 127 x 40.9 x 249</p>	<p>GT-G3063P3000VV-X.X-HV-C 3000 Watts Vout=150-400</p>	<p>GTM91120-30VV-FW 30 Watts Vout=5-48 102 x 46 x 37</p>
<p>GT-86060-06VV-X.X-W2 6 Watts Vout=5, 12 66.5 x 25.5 x 51.3</p>	<p>GT-86120-WWVV-X.X-W2 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p>GTM96180-18VV 18 Watts Vout=5-48</p>	<p>GTM91120CC-30VV-P2 30 Watts Vout=5-48</p>	<p>GT-46400-40VV-X.X 40 Watts Vout=12-48 111 x 52 x 32.3</p>	<p>GTM96900P90VV-X.X 90 Watts Vout=12-54 149.38 x 62.6 x 33.5 +/-1.0</p>	<p>GT-G3062P800VV-X.X-C 800 Watts Vout=12-60 127 x 41 x 249</p>	<p>Custom Power Supplies 1-3000 Watts</p>	<p>GTM41134-WWVV-F 6 Watts Vout=3.3-48 84.5 x 41.5 x 17.0</p>
<p>GT-83084-10VV-USB 10 Watts Vout=5-5.2 51.5 x 23.5 x 38.5 +/-0.3</p>	<p>GT-46120-12VV-X.X 12 Watts Vout=5-48 64.0 x 40.5 x 31.5</p>	<p>GTM96180-18VV 18 Watts Vout=4-48 74 x 43.5 x 36.8</p>	<p>GT-83082-3612-W2/W2E 36 Watts Vout=12 93 x 33 x 78.69 +/-0.5</p>	<p>GTM96600-60VV 60 Watts Vout=5-54 117.5 x 53.5 x 34.2</p>	<p>GTM961200P-120VV 120 Watts Vout=12-54 149.30* x 62.80 x 34.0</p>	<p>GT-G3064P1000VV-X.X-C 1000 Watts Vout=12-48 127 x 40.9 x 283</p>	<p>GTM43007-BWWVV-F 60 Watts Vout=5-48 101.6 x 50.8 x 22.5</p>	<p>GTM41080-18VV-F 18 Watts Vout=5-48 74 x 44 x 34</p>



60-450 Watts	Battery Packs	International Power Cords				
Open Frame GTM43007-AWVVV-F 60 Watts Vout=5-48 76.2 x 50.8 x 23.6 with heat sink 76.2 x 50.8 x 22.5 without heat sink	BL0105F2635161S1PCAT Lithium Polymer 3.7VDC, 105mAh Battery Pack Dimensions: 2.8 x 16.5 x 37 Configuration: 1S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified	BL1880F6835661S5PX9M Lithium Polymer 3.7VDC, 9400mAh Battery Pack Dimensions: 185.5 x 69.5 x 7.9 mm 10K NTC Thermistor BQ27200 Configuration: 1S 5P Cell Type: GP683566 Cell Shape: Rectangular IEC 62133 Certified	Type 451 North America NEMA 1-15P 10A, 13A/125V~ 	Type 302 North America NEMA 5-15P 10A, 13A/15A/125V~ 	Type 119 North America NEMA 5-15P Hospital Grade 10A, 13A/15A/125V~ 	Type 703 IEC 60320-C7 2.5A/250V~
Open Frame GTM43004P-WVVV-X-X-F 120 Watts Vout=5-48 184.0 X 62.0 X 37.5	BL0750F5030481S1PCMC Lithium Polymer 3.7VDC, 700mAh Battery Pack Dimensions: 50.5 x 30.5 x 5.3 10K NTC Thermistor Configuration: 1S 1P Cell Type: GP503048 Cell Shape: Rectangular IEC 62133 Certified UL 2054 Certified	Custom Battery Packs Contact GlobTek with your specifications 	Type 701 IEC 60320-C13 10A, 13A, 15A 125V~, 250V 	Type 712 IEC 60320-C5 2.5A, 10A/250V~ 	Type 7033 IEC 60320-C19 12A, 14A, 16A 125-250V 	Type 705 IEC 60320-C14 10A, 13A, 15A/250V~
Open Frame GTM91110P240XX 240 Watts Vout=12-55 127 x 76 x 43	BL1200P4054481S1PCAC Lithium Polymer 3.7VDC, 1200mAh Battery Pack Dimensions: 53.0 x 48.0 x 4 10K NTC Thermistor Configuration: 1S 1P Cell Type: GP404852 Cell Shape: Rectangular IEC 62133 Certified	BL2600C1865004S1PXX Lithium Ion 14.8VDC, 2600mAh Battery Pack Dimensions: 77 x 69 Fuel Gauge Configuration: 4S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified	Type PZ0800 United Kingdom BS1363 13A/250V~ 	Type 207 "Europlug" CEE7 Standard XVI (CEE 7/16) 2.5A/250V 	Type 2314 Schuko Europe CEE7 Standard sh 7 16A/250V 	Type 550 Australia, New Zealand AS/NZS 3112 10A/250V~
Open Frame GTMG3078P350VV-X-X-FW 350 Watts Vout=12-48 76.2 x 39.6 x 127	BL2200F6034501S2XXXX Lithium Ion 3.7VDC, 2200mAh Battery Pack Dimensions: 51 x 34 x 13 Configuration: 1S 2P Cell Type: 603450 Cell Shape: Rectangular IEC 62133 Certified	BL2600C1865004S1PG1 Lithium Ion 14.8VDC, 2600mAh Battery Pack Dimensions: 66 x 73.5 x 28.5 Fuel Gauge/Built In Charger Circuitry 4S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified	Type 205 India IS 1293 6A/250V~ 	Type 208 South Africa SABS 164-1 16A/250V~ 	Type 219 Argentina IRAM 2073 10A/250V~ 	Type 204B Brazil NBR 14136 10A/250V~
Open Frame GTMG3079P450VV-X-X-F 450 Watts Vout=12-48 101.6 x 39.6 x 177.8	BL2600C1865001S2PXXXX Lithium Ion 3.7VDC, 5200mAh Battery Pack Dimensions: 19 x 68.5 x 37 Configuration: 1S 2P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified	GTM91128 Smart Battery Charger Available in versions delivering 4.2V, 8.4V, or 12.6V at 1 A to address single- or multiple-battery configurations 	Type 602 China GB 1002 10A/250V~ 	Type 377C Isreal 16A/250V~ 	Type 2302 Italy CEI 23-16 10A/250V~ 	Type 2313K Korea KS C 8305 16A/250V~